

# LubeFit®

## Gasket Lubricant



### Description

LubeFit® is a vegetable fiber based lubricant for all gasketed fittings, including grooved couplings for fire sprinkler systems. It is non staining\* and does not support bacterial growth. LubeFit® can be easily applied in temperatures from 0F to 120F. LubeFit® is non-toxic and water soluble. Under normal conditions, LubeFit® is not harmful to the skin.

### Design Criteria/Data

- Water dispersible
- Applies equally well to wet or dry surfaces
- Suitable for all types of pipe lines, including potable water
- Excellent working range 0-120 degrees
- Will not support bacteria
- Will not deteriorate natural or Synthetic rubber, plastic gaskets or caston iron pipe
- FGG/BM/CZ™ System Compatible Program\*

### Application

LubeFit® should be applied in an even and thin amount over the parts to be lubricated. Avoid applying excessive amounts. The best application is achieved when applying by hand. Clean all dirt, burrs and foreign matter from the joint surfaces. Make certain the gasket is properly located. Apply an even coating of lubricant to all fitting surfaces and

gasket. Assemble the joint according to the pipe fitting manufacturer's directions.

### Disclaimer

DO NOT ALTER THE CONSISTENCY OF THIS PRODUCT. Use as is directly from the container. Keep away from your mouth and eyes. If eye contact occurs, flush with water for 5 minutes. If discomfort persists get medical attention. \*Will stain untreated porous surfaces such as concrete if not cleaned from the surface immediately.

### Specifications

#### Appearance:

Dense, paste like consistency and is light brown or tan in color.

#### Contains:

Potassium Oleate, Propylene Glycol and Mica. Contains NO PETROLEUM.

#### Packaging:

2lb (1-quart approx.)  
55-gal drum  
(400 lbs. approx.)

#### CAUTION: Eye irritant.

**Avoid contact with eyes.  
Wash thoroughly after use.**

**See Material Safety Data Sheet for additional safety and disposal information at [www.fppi.com](http://www.fppi.com)**



\*FGG/BM/CZ® System Compatible Program indicates this product has been tested by Lubrizol Advanced Materials and is monitored by Lubrizol on an on going basis to assure chemical compatibility with FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings.

© 2007 Fire Protection Products, Inc. FPPI®, LubeFit® are registered trademarks of Fire Protection Products, Inc. FGG/BM/CZ™, BlazeMaster®, FlowGuard Gold® and Corzan® are registered trademarks of Noveon IP Holdings Corp.



### Fire Protection Products, Inc

6241 Yarrow Dr., Suite A, Carlsbad, CA 92011-1541

For questions: 1 800 344-1822 • 1 800 344-3775 fax • [www.fppi.com](http://www.fppi.com)