

Description

Pipefit® Thread Sealing Paste with PTFE is a premium non-hardening PTFE filled pipe thread sealing paste designed specifically for the fire sprinkler industry. Pipefit is suitable for use on all threadable materials commonly used in fire sprinkler systems, including CPVC. Pipefit's unique blend of materials provides superior thread sealing qualities over other similarly priced sealants. The particulate PTFE also helps prevent leaks by accumulating in the voids of damaged or defective threads of the pipe or fittings. Additionally, the lubricating qualities of the PTFE and other materials in the sealing paste improve thread seating during pipe and fitting assembly. Pipefit® also adheres well to hot oily pipe present in "high speed" fabrication operations.



Design Criteria/Data

Recommended Use

Water	Air
Refrigerants	Natural Gas
Mild caustics	Steam
Kerosene	LP Gases
Acids	Gasoline
Diesel Fuel	Ammonia

Use for threaded connections on steel, stainless steel, aluminum, brass, PVC, CPVC & ABS. Operating temperature ranges -50° f to 500° f.



Spears® Compatible indicates that PipeFit® Thread Sealing Paste has been tested by Spears® Manufacturing to be compatible with Flameguard® pipe and fittings.



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings. FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation or its affiliates.



5937 DARWIN CT. SUITE 105
CARLSBAD, CA 92008
+ 1 (800) 344-1822
+ 1 (800) 344-3775 FAX

Installation

Make sure that the threads are free from burrs and other debris. Apply Pipefit® liberally to the male pipe threads. Make sure that the thread sealant is brushed into the "root" of the threads. Do not wipe off excess material until fitting has been "made on" to the pipe thread. The threading action of the fitting to the pipe will allow the proper amount of sealant to remain in the connection. Wipe off excess sealant. Pipefit® will not dry out under normal conditions. Never use dope and tape together. Keep covered when not in use to avoid contamination. Some settling of the product may occur. Occasional stirring may be necessary. Two year shelf life.

Disclaimer

DO NOT ALTER THE CONSISTENCY OF THIS PRODUCT. Use as is directly from the container. Keep away from your mouth and eyes. If eye contact occurs, flush with water for 5 minutes. If discomfort persists get medical attention.

The information contained herein is produced in good faith and is believed to be reliable but is provided for guidance and information purposes only. FPPI and its agents cannot assume liability or responsibility for results obtained in the use or misuse of its product by persons whose methods and qualifications are outside and beyond our control. It is the user's responsibility to determine the suitability of, methods of use, preparation prior to use, and appropriate installation for all products purchased from FPPI. It is the user's sole responsibility to observe and adapt such precautions as may be advisable or necessary for the protection of personnel and property in the handling and use of any of our products.

Specifications

Appearance:

Dense, paste-like consistency, off white in color.

Content Information:

PipeFit® is manufactured without asbestos in its formula.

Packaging:

16 oz. brush in cap
32 oz.
32 oz. BIC
1 gl.
5 gl.
55 gl.

CAUTION: See SDS for first aid instructions. Wash hands thoroughly after each use.

See Safety Data Sheet for additional safety and disposal information at www.fpfi.com

